

NEW

OMRON

## SMART Sensor Series

Laser Displacement Sensor CMOS Type  
Model ZX2 Series

# Stable, Easy & Affordable

New Regular-reflective Sensor Head  
Designed for Optimal Wafer Measurement



realizing


# One Solution for Any Application

Height/Length




Thin connector assembly

Level detection




Shape validation for molded parts

Warpage



Tray warpage measurement

Positioning




Robot hand positioning

Double feed



PCB double feed detection

Thickness



Wafer thickness measurement

# New

## Laser Displacement Sensor CMOS Type

### ZX2 Series

Realize stable measurements

**Resolution  $1.5\mu\text{m}^{*1}$**

Reliable measurement of moving objects

**Measurement cycle  
 $30\mu\text{s}$**

Stable Wafer Measurement **NEW**

**Regular-reflective  
Sensor Head**

Realize stable measurements at  $10\mu\text{m}$

**Linearity<sup>\*2</sup>  $0.05\%$  F.S.<sup>\*3</sup>**

Unaffected by environmental changes

**Temperature characteristic<sup>\*4</sup>  
 $0.02\%$  F.S./ $^{\circ}\text{C}^{*5}$**

<sup>\*1</sup> When employing Models ZX2-LD50/LD50L (50mm type)

<sup>\*2</sup> Linearity : Maximum error produced when measuring within measurement range

<sup>\*3</sup> A linearity of  $\pm 0.05\%$  F.S. indicates that the maximum error is  $10\mu\text{m}$  when the ZX2-LD50L is used with a 40 to 50-mm measurement range, or  $35\mu\text{m}$  when the ZX2-LD100L is used with a 65 to 100-mm measurement range.

<sup>\*4</sup> Temperature characteristic : Error produced when the ambient temperature varies by  $1^{\circ}\text{C}$

<sup>\*5</sup> Linearity  $\pm 0.02\%$  F.S./ $^{\circ}\text{C}$  indicates the maximum error is  $4\mu\text{m}$  when the ambient temperature varies by  $1^{\circ}\text{C}$  in the case of using Models ZX2-LD50/LD50L with a measurement range  $\pm 10\text{mm}$ .




# Stable Measurement and Easy to Use

Stability

## Stable measurements in case of color/material and moving objects


### Dynamic range of two million times

Stable measurements are enabled for any color or surface condition, including metals, substrates, elastomers, and transparent materials, through OMRON's unique HSDR-CMOS (High Speed and Dynamic Range) image sensor and a step-less laser power adjustment algorithm.




### Step-less adjustment of laser power



For high reflectance, brightly colored workpiece



For low reflectance, darkly colored workpiece




### Stable measurements on objects with changing color/material



A line beam is used in addition to an emitter beam when dealing with rough surfaces to average out the amount of reflected light and to offset the amount of light received at a high-speed measurement period of 30  $\mu$ s in order to reduce variations in received light and to enable stable measurements for moving objects.

### Stable measurements on moving objects



Note. Typical value of the ZX-LD50L. The resolution, angle characteristic, measuring range, linearity, spot diameter, and other specifications differ among models. Refer to *Ratings and Specifications* for details. The linearity indicates the error with respect to the ideal straight line of the displacement output in the case of measuring Omron's standard target object. Linearity and measured value may vary depending on target object. Before final installation, test the sensor required for the application to validate that the desired measurements have been obtained.

Easy

## Easy and User-friendly Configuration

### Smart tuning

The ideal configuration for stable measurements is realized by a single button through the new feature "smart tuning", and no longer depends on the skill of the user. A reliable configuration is achieved by three tuning methods, which can be selected to match the type of object and surface conditions to be measured.

Sensor configuration by just a pushing the SMART button



### Three selectable tunings

#### One type of workpiece




**Single smart tuning**  
Best configuration for stable detection in case of objects do not change by pushing the button for one second

#### Several types of workpiece



**Multi-smart tuning**  
Ideal configuration for stable detection of changing objects by pushing the button for three seconds

#### Surface conditions of the workpiece are variable



**Active smart tuning**  
Continuous configuration improvement for the stable detection of all locations by pushing the button for five seconds

# Sensor Heads for Various Applications-select the Range and Type of Beam


New Regular-reflective Sensor Head Designed for Optimal Wafer Measurement

## ZX2-LD50L Line beam type ZX2-LD50 Spot beam type

|                     |                                                                          |
|---------------------|--------------------------------------------------------------------------|
| ● Measurement range | 50mm±10mm                                                                |
| ● Resolution        | 1.5μm                                                                    |
| ● Linearity         | Line beam ±0.05%F.S.* <sup>1</sup><br>Spot beam ±0.10%F.S.* <sup>1</sup> |
| ● Beam size         | Line beam Approx.60μm×2.6mm<br>Spot beam Approx.60μm dia.                |

### Spot beam

Precise measurement on micro-scale objects




## ZX2-LD50V Spot beam type (regular-reflective)

|                     |                            |
|---------------------|----------------------------|
| ● Measurement range | 48mm±5mm                   |
| ● Resolution        | 1.5μm                      |
| ● Linearity         | Spot beam ±0.3%F.S.        |
| ● Beam size         | Spot beam Approx.60μm dia. |

### Regular-reflective

Stable wafer measurement




## ZX2-LD100L Line beam type ZX2-LD100 Spot beam type

|                     |                                                                          |
|---------------------|--------------------------------------------------------------------------|
| ● Measurement range | 100mm±35mm                                                               |
| ● Resolution        | 5μm                                                                      |
| ● Linearity         | Line beam ±0.05%F.S.* <sup>2</sup><br>Spot beam ±0.10%F.S.* <sup>2</sup> |
| ● Beam size         | Line beam Approx.110μm×2.7mm<br>Spot beam Approx.110μm dia.              |

### Line beam

Stable measurement on rough-surfaced objects



\*<sup>1</sup> Using 40 to 50mm  
\*<sup>2</sup> Using 65 to 100mm



## Support for Various Environments/Space-Saving ●●● The Smart Sensor Head

### Reliable measurements in harsh environments

IP67, robot cable  
& temperature characteristic 0.02% F.S./°C

IP67 protection class enables to use the sensor in harsh environments. A robot cable is used as standard between the head and amplifier, that the unit can be used reliably on moving parts. In addition, as 3D UV bond is used to fix the optical components rather than screws, stress can be controlled and a temperature characteristic 0.02% F.S./°C\* is realized.

\* If the room temperature varies 1°C, the measured value varies 0.02% F.S.  
(corresponding to 4μm for the Model ZX2-LD50)



### Compact sensor for easy mounting

World smallest\*

The world's smallest CMOS laser displacement sensor head is realized in a resin case. Enables to mount the sensor in smallest spaces and to minimize measurement errors arising from temperature fluctuations.

\* According to OMRON investigation of CMOS laser displacement sensors performed in September 2010.




### 10μm precision measurements

Linearity to meet the application


Measurements to an even higher accuracy are realized for applications that do not require the entire measurement range. If the range of the field is less than the length of the measurement center, linearity accuracy improves by 50% compared with that for the full range.\*

\* For the ZX2-LD50L/LD100L.

Model ZX2-LD50L



Example of an application that does not require the entire measurement range  
Low-profile connector assembly height measurement



Example of an application that requires the entire measurement range  
Robot hand registration

### Visualization to prevent from stopping the production-line


Laser life display function

The end of the laser diode lifespan is automatically detected and displayed so maintenance can be performed systematically. On the main digital display of the amplifier, this is indicated by an LED on the back of the head. Accordingly, in case of amplifier is within the control panel, the lifetime can be confirmed by the head and the indications are not missed.




## Ease of Use by “LED Display” and “Calculating Unit”

### 11-segment LED display for intuitive configuration



### Easy calculations of measurements





# A thorough pursuit of user-friendliness ●●● The Smart Amplifier Unit


## No need for a manual

### 11 Segment LED Display

An 11 segment LED display is integrated in the compact housing. Alphanumeric characters can be read with ease and there is no need to refer to a manual.



Comparison of the existing 7 segment LED display and the 11 segment LED display





The compact housing stays just as it is

## Perform two calculations with ease

### Thickness + subtraction mode

The calculated results of two sensor heads are displayed on the amplifier unit by just connecting the calculating unit between the two amplifier units. The calculation function can be chosen from the two modes of thickness and subtraction. It is also possible to prevent mutual interference by coupling via the calculating units. (Up to five amplifier units can be connected.)




## Easy change of setup

### Equipped with 4 banks

The amplifier unit is equipped with four bank functions. Easy change of setup between four modes is supported by just switching between the bank functions.

Existing models




ZX2



# One Sensor for Any Measurement Application

## Height/ Length

Height measurements prior  
to IC package sealing




### Point

Stable measurements can be performed by the HSDR-CMOS image sensor and Omron's proprietary algorithm, even for measurements on moving IC packages.

## Level detection

Shape validation  
for molded parts




### Point

Calculation of the measured values can be carried out and the difference in level can be easily measured by just connecting the calculating unit between two amplifiers. Even if the surface conditions of a molded part varies, application of a line beam and HSDR-CMOS image sensor results in almost no fluctuation in measured value.

## Warpage

Tray warping measurement  
before chip baking




### Point

Even if there is temperature variation due to the ambient temperature, a die-cast is used for the optical base and so there is almost no fluctuation in measured value.

## Positioning

Robot hand Positioning




### Point

Stable measurements can be performed by the HSDR-CMOS image sensor and Omron's proprietary algorithm even for robot hand registration.

## Double feed

PCB double feed detection




### Point

Even if the color of the substrate changes, application of the HSDR-CMOS image sensor and Omron's proprietary algorithm results in almost no fluctuation in measured value.

## Thickness

Wafer thickness  
measurement






### Point

You can easily measure thicknesses by using Regular-reflective Sensor Heads and connecting a Calculating Unit between the two Amplifier Units to perform calculations.

## Ordering Information

### Units

#### Sensor Heads [\[Dimensions → page 14\]](#)

| Appearance                                                                        | Optical system     | Beam shape | Sensing distance                                                                                      | Resolution | Model           |
|-----------------------------------------------------------------------------------|--------------------|------------|-------------------------------------------------------------------------------------------------------|------------|-----------------|
|  | Diffuse reflective | Line beam  |  50±10mm<br>40 60    | 1.5μm      | ZX2-LD50L 0.5M  |
|                                                                                   |                    | Spot beam  |                                                                                                       |            | ZX2-LD50 0.5M   |
|                                                                                   |                    | Line beam  |  100±35mm<br>65 135 | 5μm        | ZX2-LD100L 0.5M |
|                                                                                   |                    | Spot beam  |                                                                                                       |            | ZX2-LD100 0.5M  |
|                                                                                   | Regular reflective | Spot beam  |  48±5mm<br>43 53     | 1.5μm      | ZX2-LD50V 0.5M  |

#### Amplifier Units [\[Dimensions → page 14\]](#)

| Appearance                                                                        | Power supply | Output type | Model        |
|-----------------------------------------------------------------------------------|--------------|-------------|--------------|
|  | DC           | NPN         | ZX2-LDA11 2M |
|                                                                                   |              | PNP         | ZX2-LDA41 2M |

**Accessories (sold separately)** These are not included with the Sensor Head or Amplifier Unit. Please order as necessary.

#### Calculating Unit [\[Dimensions → page 14\]](#)

| Appearance                                                                         | Model   |
|------------------------------------------------------------------------------------|---------|
|  | ZX2-CAL |

#### Communications Interface Unit [\[Dimensions → page 14\]](#)

| Appearance                                                                          | Type    | Model    |
|-------------------------------------------------------------------------------------|---------|----------|
|  | RS-232C | ZX2-SF11 |

#### Sensor Head Extension Cables [\[Dimensions → page 14\]](#)

| Cable Length | Model     |
|--------------|-----------|
| 1m           | ZX2-XC1R  |
| 4m           | ZX2-XC4R  |
| 9m           | ZX2-XC9R  |
| 20m          | ZX2-XC20R |

\* Extension cables cannot be coupled and used together.

#### Mounting Brackets [\[Dimensions → page 15\]](#)

| Applicable Sensor Heads            | Appearance                                                                          | Model    | Contents                                                          |
|------------------------------------|-------------------------------------------------------------------------------------|----------|-------------------------------------------------------------------|
| ZX2-LD50V<br>ZX2-LD50L<br>ZX2-LD50 |  | E39-L178 | Mounting Bracket: 1<br>Nut plate: 1<br>Phillips screws (M3×30): 2 |
| ZX2-LD100L<br>ZX2-LD100            |  | E39-L179 |                                                                   |

## Diffuse-reflective Sensor Heads

| Item                               | Model                                                                                                                         | ZX2-LD50L                                           | ZX2-LD50 | ZX2-LD100L                                           | ZX2-LD100                                            |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------|----------|------------------------------------------------------|------------------------------------------------------|
| Optical system                     | Diffuse reflective                                                                                                            |                                                     |          |                                                      |                                                      |
| Light source<br>(wave length)      | Visible-light semiconductor laser with a wavelength of 660 nm and an output of 1mW max.                                       |                                                     |          |                                                      |                                                      |
|                                    | EN class 2,FDA class 2*5                                                                                                      |                                                     |          |                                                      |                                                      |
| Measurement center point           | 50mm                                                                                                                          |                                                     |          | 100mm                                                |                                                      |
| Measurement range                  | ±10mm                                                                                                                         |                                                     |          | ±35mm                                                |                                                      |
| Beam shape                         | Line                                                                                                                          | Spot                                                |          | Line                                                 | Spot                                                 |
| Beam size *1                       | Approx. 60μm×2.6mm                                                                                                            | Approx. 60μm dia.                                   |          | Approx.110μm×2.7mm                                   | Approx.110μm dia.                                    |
| Resolution *2                      | 1.5μm                                                                                                                         |                                                     |          | 5μm                                                  |                                                      |
| Linearity *3                       | ±0.05%F.S. (40 to 50mm)<br>±0.1%F.S. (entire range)                                                                           | ±0.1%F.S. (40 to 50mm)<br>±0.15%F.S. (entire range) |          | ±0.05%F.S. (65 to 100mm)<br>±0.1%F.S. (entire range) | ±0.1%F.S. (65 to 100mm)<br>±0.15%F.S. (entire range) |
| Temperature characteristic *4      | 0.02%F.S./°C                                                                                                                  |                                                     |          |                                                      |                                                      |
| Ambient illumination               | Incandescent lamp: 10,000lx max. (on light receiving side)                                                                    |                                                     |          |                                                      |                                                      |
| Ambient temperature                | Operating: 0 to +50°C, Storage: -15 to +70°C (with no icing or condensation)                                                  |                                                     |          |                                                      |                                                      |
| Ambient humidity                   | Operating and storage: 35% to 85% (with no condensation)                                                                      |                                                     |          |                                                      |                                                      |
| Dielectric strength                | 1,000 VAC, 50/60 Hz for 1 minute                                                                                              |                                                     |          |                                                      |                                                      |
| Vibration resistance (destruction) | 10 to 150 Hz, 0.7-mm double amplitude, 80 minutes, each in X,Y,and Z directions                                               |                                                     |          |                                                      |                                                      |
| Shock resistance (destruction)     | 300 m/s² 3 times each in six directions (up/down,left/right,forward/backward)                                                 |                                                     |          |                                                      |                                                      |
| Degree of protection               | IEC60529, IP67                                                                                                                |                                                     |          |                                                      |                                                      |
| Connection method                  | Connector connection (standard cable length: 500 mm)                                                                          |                                                     |          |                                                      |                                                      |
| Weight (packed state)              | Approx.160g (Sensor Head only: Approx.75g)                                                                                    |                                                     |          |                                                      |                                                      |
| Materials                          | Case and cover: PBT (polybutylene terephthalate), Optical window: Glass, Internal thread: Brass, Cable: PVC                   |                                                     |          |                                                      |                                                      |
| Accessories                        | Instruction sheet, Ferrite core x1 (made by TDK Corp. ZCAT1730-0730A), Laser warning label (English), FDA certification label |                                                     |          |                                                      |                                                      |

## Regular-reflective Sensor Head

| Item                               | Model                                                                                                                         | ZX2-LD50V |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------------|-----------|
| Optical system                     | Regular reflective                                                                                                            |           |
| Light source (wave length)         | Visible-light semiconductor laser with a wavelength of 660 nm and an output of 0.24 mW max. EN class 1, FDA class 1*5         |           |
| Measurement center point           | 48mm                                                                                                                          |           |
| Measurement range                  | ±5mm                                                                                                                          |           |
| Beam shape                         | Spot                                                                                                                          |           |
| Beam size *1                       | Approx. 60μm dia.                                                                                                             |           |
| Resolution *2                      | 1.5μm                                                                                                                         |           |
| Linearity *3                       | ±0.3%F.S. (entire range)                                                                                                      |           |
| Temperature characteristic *4      | 0.06%F.S./°C                                                                                                                  |           |
| Ambient illumination               | Incandescent lamp: 10,000lx max. (on light receiving side)                                                                    |           |
| Ambient temperature                | Operating: 0 to +50°C, Storage: -15 to +70°C (with no icing or condensation)                                                  |           |
| Ambient humidity                   | Operating and storage: 35% to 85% (with no condensation)                                                                      |           |
| Dielectric strength                | 1,000 VAC, 50/60 Hz for 1 minute                                                                                              |           |
| Vibration resistance (destruction) | 10 to 150 Hz, 0.7-mm double amplitude, 80 minutes, each in X,Y,and Z directions                                               |           |
| Shock resistance (destruction)     | 300 m/s <sup>2</sup> 3 times each in six directions (up/down,left/right,forward/backward)                                     |           |
| Degree of protection               | IEC 60529, IP67                                                                                                               |           |
| Connection method                  | Connector connection (standard cable length: 500 mm)                                                                          |           |
| Weight (packed state)              | Approx. 160g (Sensor Head only: Approx. 75g)                                                                                  |           |
| Materials                          | Case and cover: PBT (polybutylene terephthalate), Optical window: Glass, Internal thread: Brass, Cable: PVC                   |           |
| Accessories                        | Instruction sheet, Ferrite core x1 (made by TDK Corp. ZCAT1730-0730A), Laser warning label (English), FDA certification label |           |

Note) False detection outside the measurement range can occur in the case of an object with high reflectance.

\*1. Beam size: Defined as 1/e<sup>2</sup> (13.5%) of the central intensity at the smallest value of diameter for the measurement range (typical value)

False detections can occur in the case there is light leakage outside the defined region and the surroundings of the target object have a high reflectance in comparison to the target object.

\*2. Resolution: indicates the degree of fluctuation (±3σ) of analog output when connected to the ZX2-LDA.

(The measured value is given for the center distance for OMRON's standard target object (diffuse-reflective models: white ceramic object, regular-reflective models: 1/4 λ flat mirror) when the response time of the ZX2-LDA is set to 128 ms.)

Indicates the repetition accuracy for when the workpiece is in a state of rest. Not an indication of distance accuracy.  
Resolution performance may not be satisfied in a strong electromagnetic field.

\*3. Linearity: indicates the error with respect to the ideal straight line of the displacement output in the case of measuring Omron's standard target object. Linearity and measured value may vary depending on target object.

F.S. indicates the full scope of the measurement range. (ZX2-LD50 (L): 20mm)

\*4. Temperature characteristic: Value for the case the space between the sensor head and Omron's standard target object is secured by an aluminum jig. (Measured at the measurement center distance)

\*5. These Sensors are classified as Class 2 laser devices for diffuse-reflective models and Class 1 for regular-reflective models under IEC 60825-1 and the regulations of Laser Notice No. 50 for FDA certification. CDRH registration has been completed.

## Amplifier Units

| Item                                                                     | Model | ZX2-LDA11                                                                                                                                                                                                                                                                                                                                                      | ZX2-LDA41                                                                                                                                  |
|--------------------------------------------------------------------------|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------|
| Measurement period *1                                                    |       | Min. 30μs                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                                            |
| Response time                                                            |       | 60μs, 120μs, 240μs, 500μs, 1ms, 2ms, 4ms, 8ms, 12ms, 20ms, 36ms, 66ms, 128ms, 250ms, 500ms                                                                                                                                                                                                                                                                     |                                                                                                                                            |
| Analog output *2                                                         |       | 4 to 20 mA, Max. load resistance: 300Ω, ±5VDC or 1 to 5 VDC, Output impedance: 100Ω                                                                                                                                                                                                                                                                            |                                                                                                                                            |
| Judgement outputs (HIGH/PASS/LOW: 3 outputs), error output               |       | NPN open-collector outputs, 30 VDC, 50 mA max. (residual voltage: 1V max. for load current 10mA max., 2V max. for load current above 10mA)                                                                                                                                                                                                                     | PNP open-collector outputs, 30 VDC, 50 mA max. (residual voltage: 1V max. for load current 10mA max., 2V max. for load current above 10mA) |
| Laser OFF input, zero reset input, timing input, reset input, bank input |       | ON: Short-circuited with 0-V terminal or 1.2V or less<br>OFF: Open (leakage current: 0.1 mA max.)                                                                                                                                                                                                                                                              | ON: Supply voltage short-circuited or supply voltage within -1.2V<br>OFF: Open (leakage current: 0.1 mA max.)                              |
| Functions                                                                |       | Smart tuning, scaling, sample hold, peak hold, bottom hold, peak-to-peak hold, self-peak hold, self-bottom hold, average hold, zero reset, On-delay timer, OFF-delay timer, keep/clamp switch, (A-B)calculations *3, thickness calculation *3, mutual interference prevention *3, laser deterioration detection, bank function(4 banks), differential function |                                                                                                                                            |
| Indications                                                              |       | Judgement indicators: HIGH(orange),PASS(green),LOW(orange),11-segment main display(red),11-segment sub-display(orange),laser ON(green),zero reset(green),enable(green),menu(green), HIGH threshold(orange),LOW threshold(orange)                                                                                                                               |                                                                                                                                            |
| Power supply voltage                                                     |       | 10 to 30 VDC, including 10% ripple(p-p)                                                                                                                                                                                                                                                                                                                        |                                                                                                                                            |
| Power consumption                                                        |       | 3,000 mW max. (at 24 VDC: 125 mA max., at 12 VDC: 250 mA max.)                                                                                                                                                                                                                                                                                                 |                                                                                                                                            |
| Ambient temperature                                                      |       | Operating: 0 to +50°C, Storage: -15 to +70°C (with no icing or condensation)                                                                                                                                                                                                                                                                                   |                                                                                                                                            |
| Ambient humidity                                                         |       | Operating and storage: 35% to 85% (with no condensation)                                                                                                                                                                                                                                                                                                       |                                                                                                                                            |
| Dielectric strength                                                      |       | 1,000 VAC, 50/60 Hz for 1 minute                                                                                                                                                                                                                                                                                                                               |                                                                                                                                            |
| Vibration resistance (destruction)                                       |       | 10 to 150 Hz, 0.7-mm double amplitude, 80 minutes, each in X,Y,and Z directions                                                                                                                                                                                                                                                                                |                                                                                                                                            |
| Shock resistance (destruction)                                           |       | 300 m/s <sup>2</sup> 3 times each in six directions (up/down,left/right,forward/backward)                                                                                                                                                                                                                                                                      |                                                                                                                                            |
| Degree of protection                                                     |       | IEC60529, IP40                                                                                                                                                                                                                                                                                                                                                 |                                                                                                                                            |
| Connection method                                                        |       | Prewired (standard cable length: 2 m)                                                                                                                                                                                                                                                                                                                          |                                                                                                                                            |
| Weight (packed state)                                                    |       | Approx.200g (Amplifier Unit only: Approx.135g)                                                                                                                                                                                                                                                                                                                 |                                                                                                                                            |
| Materials                                                                |       | Case: PBT (polybutylene terephthalate), Cover: Polycarbonate, Display: Methacrylic resin, Button: Polyacetal, Cable: PVC                                                                                                                                                                                                                                       |                                                                                                                                            |
| Accessories                                                              |       | Instruction sheet                                                                                                                                                                                                                                                                                                                                              |                                                                                                                                            |

\*1. In the case of Omron's standard target object (white ceramic)

\*2. Configure current output (4 to 20mA) and voltage output (±5V or 1 to 5V) by MENU mode.

\*3. Calculating unit (ZX2-CAL) is necessary. Calculations are possible for two amplifier units. Mutual interference prevention is possible for up to five amplifier units.

## Calculating Unit


| Item                               | Model | ZX2-CAL                                                                                     |
|------------------------------------|-------|---------------------------------------------------------------------------------------------|
| Applicable Amplifier Units         |       | ZX2-LDA11, ZX2-LDA41                                                                        |
| Current consumption                |       | 12 mA max. (supplied from the Smart Sensor Amplifier Unit)                                  |
| Ambient temperature                |       | Operating: 0 to +50°C, storage: -15 to +70°C (with no icing or condensation)                |
| Ambient humidity                   |       | Operating and storage: 35% to 85% (with no condensation)                                    |
| Connection method                  |       | Connector                                                                                   |
| Dielectric strength                |       | 1,000 VAC, 50/60 Hz for 1 minute                                                            |
| Vibration resistance (destructive) |       | 10 to 150 Hz, 0.7-mm double amplitude, 80 minutes, each in X,Y,and Z directions             |
| Shock resistance (destructive)     |       | 300 m/s <sup>2</sup> 3 times each in six directions (up/down, left/right, forward/backward) |
| Materials                          |       | Case: ABS, Display: Methacrylic resin                                                       |
| Weight (packed state)              |       | Approx. 50g (Calculating Unit only: Approx. 15g)                                            |
| Accessories                        |       | Instruction sheet                                                                           |

## ZX2-series Communications Interface Unit


| Item                               | Model                  | ZX2-SF11                                                                                                                                                                  |
|------------------------------------|------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Power supply voltage               |                        | 10 to 30 VDC ±10% (including 10% ripple (p-p)) (Supplied from Sensor Amplifier.)                                                                                          |
| Power consumption                  |                        | 720 mW max. (at 24 V: 30 mA max., at 12 V: 60 mA max.) (Not including Sensor Amplifier current consumption or output current.)                                            |
| Applicable Amplifier Units         |                        | ZX2-LDA□□ (Production after November 2013)                                                                                                                                |
| Applicable Amplifier Unit versions |                        | Sensor Amplifier Unit version: V1.330 or higher (The Sensor Amplifier version is shown on the sub-digital display when the power of the Sensor Amplifier is turned ON.)   |
| Max. No. of Amplifier Units        |                        | 5                                                                                                                                                                         |
| Communications functions           | Port                   | RS-232C (9-pin, D-Sub connector)                                                                                                                                          |
|                                    | Communications method  | Full duplex                                                                                                                                                               |
|                                    | Synchronization method | Start/stop synchronization                                                                                                                                                |
|                                    | Transmission code      | ASCII                                                                                                                                                                     |
|                                    | Baud rate              | 38,400 (at shipping)/9,600 bps switchable                                                                                                                                 |
|                                    | Data bit length        | 8 bits                                                                                                                                                                    |
|                                    | Parity check           | None                                                                                                                                                                      |
|                                    | Stop bit length        | 1 bit                                                                                                                                                                     |
| Data delimiter                     | Receiving              | CR or CR + LF is automatically recognized.                                                                                                                                |
|                                    | Sending                | CR + LF fixed                                                                                                                                                             |
| Indicators                         |                        | Power supply: green, Sensor communications: green, Sensor communications error: red, External terminal communications: green, External terminal communications error: red |
| Protective circuits                |                        | Power supply reverse polarity protection                                                                                                                                  |
| Ambient temperature                |                        | Operating: 0 to 50°C, storage: -15 to 60°C (with no icing or condensation)                                                                                                |
| Ambient humidity                   |                        | Operating and storage: 35% to 85% (with no condensation)                                                                                                                  |
| Insulation resistance              |                        | 20 MΩ min. (at 500 VDC)                                                                                                                                                   |
| Dielectric strength                |                        | 1,000 VAC, 50/60 Hz for 1 min, Leakage current: 10 mA max.                                                                                                                |
| Materials                          |                        | Case: PBT (polybutylene terephthalate), Cover: Polycarbonate                                                                                                              |
| Accessories                        |                        | Instruction sheet, 2 clamps                                                                                                                                               |

# Engineering Data (Reference Value)

## Angle Characteristic




## Linearity Characteristic for Different Materials



\* The x-axis displacement indicates the measurement distance displayed by the amplifier unit. The measurement distance displayed by the amplifier unit takes the measurement center distance as 0 and displays the near-side from the sensor as plus and the far-side as minus.


## Angle Characteristic

### ZX2-LD50V



## Linearity Characteristic for Different Materials

### ZX2-LD50V



\* The x-axis displacement indicates the measurement distance displayed by the amplifier unit. The measurement distance displayed by the amplifier unit takes the measurement center distance as 0 and displays the near-side from the sensor as plus and the far-side as minus.


## Dimensions

(Unit: mm)

### Units

#### Sensor Heads


ZX2-LD50/ZX2-LD50L  
ZX2-LD100/ZX2-LD100L  
ZX2-LD50V



\* In the case of ZX2-LD50 (L), L=50, A=21°  
In the case of ZX2-LD100 (L), L=100, A=11.5°

#### Amplifier Units


ZX2-LDA11/ZX2-LDA41



### Accessories (sold separately)


#### Calculating Unit

ZX2-CAL




#### ZX2-series Communications Interface Unit

ZX2-SF11



#### Sensor Head Extension Cables


ZX2-XC1R  
ZX2-XC4R  
ZX2-XC9R  
ZX2-XC20R



\* Length L is as follows.  
ZX2-XC1R: 1 m, ZX2-XC4R: 4 m,  
ZX2-XC9R: 9 m, ZX2-XC20R: 20 m  
Minimum bending radius: 30 mm  
Note: Attach the enclosed ferrite cores (16.5 dia., length: 30 mm) within 100 mm of each end of the extension cable.


## Mounting Bracket

E39-L178



## Mounting Bracket


E39-L179



\* Use this Mounting Bracket when installing the ZX2-LD100 (L) as a normal Diffuse-reflective or Regular-reflective Sensor Head.


## Installation Method for Regular-reflective Sensor Head

Using a E39-L178 Mounting Bracket:



## Installation Method for Regular-reflective Sensor Heads (Installing a Diffuse-reflective Sensor Head as a Regular-reflective Sensor Head)


Using a E39-L179 Mounting Bracket:



## Not Using a Mounting Bracket:



Tilt the Sensor Head towards the workpiece as shown below.

ZX2-LD50V



## Installation Method for Diffuse-reflective Sensor Heads

### Using a E39-L178, E39-L179 Mounting Bracket:




\*1 The measurement distance reference position is the Sensor's sensing surface.

Note: When securing the Sensor Head in the Mounting Bracket, insert the screws into the side of the Sensor Head where the warning label is located and secure the Sensor Head into place.

### Not Using a Mounting Bracket:

Mount the Sensor Head in relation to the workpiece as shown below.



\* ZX2-LD50 (L): 50  
ZX2-LD100 (L): 100